



REFLECTIVE INSULATION

Reduces your carbon footprint.

ESP Low-E Insulation is simple to install & environmentally friendly. By providing high R-values either stand alone or in conjunction with mass insulations Low-E can help increase energy savings.



Low-E can be used in all facets of the building industry where conventional insulations are used. It can be used alone or in conjunction with mass insulations for high r-systems. From large commercial buildings, light gauge steel to post frame structures. Low-E can be used to save money on heating and cooling costs. ESP LOW-E® Insulation is easy to handle and will not tear or puncture easily. It is flexible and seals tight around fasteners. With our Foil, White Foil or Black Foil facings and our EZ Seal Tab, Staple Flange or Trimmed edges to go with them, we have the products to make your building as energy efficient as possible while promoting a healthier indoor environment.



BENEFITS OF LOW-E INSULATION:

- Increases energy savings
- Non-toxic, no fiberglass – no itching
- Excellent vapor barrier
- Installs easily with razor knife and foil tape
- All Testing Current and Available
- Superior thermal performance
- Flexible and durable
- Improves insulation system performance
- Insect/Bird resistant
- Great for new construction or retrofits

* The information contained herein pertains to only the product codes listed on the reverse side of this flyer.

Low-E Insulation is manufactured using either a scrim reinforced foil facing or by using a foil facing without scrim reinforcement. The latter product is known as Econo-E®. All foil facings are 99.4% Polished Aluminum.

PRODUCT NAME – ESP LOW-E® Insulation
PRODUCT CODES – 4LFLS, 4LFLT
FINISHED DIMENSION – 48" w x 125' l (standard)
CORE MATERIAL – Polyethylene
FACINGS AVAILABLE – Foil/Foil
EDGINGS AVAILABLE: Trimmed, Staple Flange
FLAME AND SMOKE – ASTM E 84
FLAME SPREAD: Less than 25, Smoke Developed: Less than 50
NFPA 286 - Foil/Foil Passed
R-VALUE – Up to R-11*

PRODUCT NAME – ESP Econo-E® Insulation
PRODUCT CODES – 4EFES, 4EFET, 4EFEZ, 4EFKZ, 4EFWS, 4EFWT, 4EFWZ
FINISHED DIMENSION – 48" w x 125' l (standard)
CORE MATERIAL – Polyethylene
FACINGS AVAILABLE – Foil/Foil, Foil/Black Foil, Foil/White foil
EDGINGS AVAILABLE: Trimmed, Staple Flange, EZ Seal
FLAME AND SMOKE – ASTM E 84
FLAME SPREAD: Less Than 25, Smoke Developed: Less Than 50
NFPA 286 - Foil/White Foil Passed
R-VALUE – Up to R-11*

* R-values may vary depending on facing assembly

For detailed testing information please contact us at 1-800-289-5693.

Do not leave this product exposed on walls or ceilings where ceilings are under 10'. Areas under 10' should be covered with a proper thermal barrier. See your local Code Official for more information.

WARNING: Although ESP LOW-E® Insulation Products are all ASTM fire tested; it is recommended that they or any insulation material should not be exposed to open flame or other ignition sources of sufficient intensity during shipment, storage or installation.

Caution: Aluminum is an Electrical Conductor. Please use caution when working around electrical sources including overhead power lines.

Edgings Available:



Discover even more ways to lower energy costs with ESP LOW-E® Insulation



LOW-E
REFLECTIVE INSULATION
Reduces your carbon footprint.

Green building is not just a trend, but the wave of the future as more and more homeowners and builders demand energy efficient homes and products. ESP LOW-E® Insulation products are designed for maximum energy and cost efficiency. Whether it's under slab, under roof, around duct work or wrapping the entire house, ESP LOW-E® Reflective Insulation products save more money on heating and cooling than regular insulation and housewrap.

Check out all the ways ESP LOW-E® Insulation can help reduce your energy consumption around the home.

ESP LOW-E® Insulation • ESP LOW-E® Housewrap • ESP LOW-E® SlabShield

For more information and a free sample of LOW-E material, or for the dealer nearest you visit www.low-e.com or call 1.800.289.5693

ESP LOW-E is a trademark of Environmentally Safe Products, Inc.

1.2008.8034

