



1500 West Shure Drive
Arlington Heights, IL 60004
(800) 527-9948 FAX: (847) 506-6195
www.cetco.com

April 1, 2007

STRONGSEAL DB LEED™ PRODUCT INFORMATION

StrongSeal DB is a high-performance nail-down rubber roofing underlayment membrane derived from recycled tire crumb rubber and other proprietary products and features no asphalt. The underlayment membrane shall be installed over the field of the roof deck prior to common exterior roofing materials like architectural shingles, slate, tile, shake and metal roofs. The membrane underlayment shall also be capable of being used at such areas as parapet walls behind EFIS or stucco architectural finish systems.

MANUFACTURING LOCATION

CETCO certifies that StrongSeal DB is manufactured in West Unity, OH. If your project falls within a 500-mile radius of this location, the product is considered to be locally produced material and can help contribute to earning Materials & Resources – Credit 5.1 and Credit 5.2.

RECYCLED CONTENT

CETCO certifies that StrongSeal DB is manufactured with total 89% recycled content by weight; with 45% post-consumer recycled material by weight, and 44% post-industrial recycled content by weight. Batch to batch variations in manufacturing operations to ensure product performance properties will result in minimal variations from the above listed figure. StrongSeal DB can help contribute to earning Materials & Resources – Credit 4.1 and Credit 4.2.

VOC CONTENT

CETCO certifies that StrongSeal DB contains 0 g/L Volatile Organic Compounds (VOCs).

CETCO is committed to the use of recycled content in the manufacturing of StrongSeal DB and supports the United States Green Building Council (USGBC) by participating as a USGBC Industry Member.

Sincerely,

A handwritten signature in black ink, appearing to read "Stacy Byrd".

Stacy Byrd
National Products Manager



"LEED" is a trademark of the U.S. Green Building Council